

Technical Specifications

Parameters	Value
Motor RPM	1400
Cooling Area*	15 sq.mt / 150 sq.ft
Air throw Distance*	10 mt. / 33 ft.
Air delivery	1100 m ³ .hr / 650 cfm
Electrical*	
<u>230V / 50-60 Hz</u>	
Wattage	80 W
Max. Current	0.40 amp
<u>110V / 60Hz</u>	
Wattage	90 W
Max. Current	0.80 amp
Blower / Fan	Blower
Blower Diameter	132 mm / 5 inch
Speed Control	Three
Water tank capacity	16 ltr / 4.25 gallons (US)
Portability	Castors
Vertical louvre movement	Automatic
Humidity Control	Yes
Dust filter net	Yes
Water Level Indicator	Yes
Cooling Media	Aspen
Dimensions (Product)	
Length	450 mm / 18 inch
Breadth	287 mm / 11 inch
Height	653 mm / 26 inch
Dimensions (Carton)	
Length	493 mm / 19 inch
Breadth	329 mm / 13 inch
Height	700 mm / 28 inch
Weight	
Product	10 kg / 22 lbs
Incl. Packaging	12kg / 26 lbs
Certifications	CE, SASO
No.of units per 40 ft container (HC)	644

* Under test conditions, actual may vary depending on the ambient conditions and the heat load. All specifications are approximate and may vary within $\pm 10\%$ of the specified value. All products are subject to continuous improvement. The company reserves the right to change specifications without any prior notice.



Seal of Conformity with European directives



Saudi Arabian Standards Organisation




www.symphonycomfort.com
e-mail: international@symphonycomfort.com

Portable Evaporative Air Cooler

Surröund

Cools upto 15 sq.mt. / 150 sq.ft.*



Air coolers with Lowest Power Consumption



With three side
cooling pads
this air cooler is ideal for...



Kids Room



Study Room



Office



Coastal Area

Surround

Cools upto 15 sq.mt. / 150 sq.ft.*

With cooling pads on three sides for the first time ever in its category, Surround is truly the most compact and powerful. So, surrender...



**Low power consumption of
only 80 watts / 0.08 units per hour***

- **Three side wood wool cooling pads for great cooling**



- **Humidity control**



- **Large tank capacity**



- **10 mt. (33 ft.)* air throw**



- **3 Speed motor**



* Wattage at 230/50-60 Hz